

WebStencils in Delphi: Your First Server-Rendered HTML Page

An introduction to WebStencils, the template engine that ships with Delphi since RAD Studio 12.2 -- we add an HTML page with a layout, a loop, and a condition to the WebBroker server from the previous post.

By Dr. Holger Flick



In [the previous post](#), we built a small REST server with WebBroker and nothing else from outside the Delphi box. It answers JSON, which is exactly what a JavaScript front end or a mobile app wants. However, quite a few web applications do not need a separate front end at all. A dashboard for the support team, an admin page for a service, a status page -- in many cases, HTML rendered on the server is the simplest thing that could possibly work.

For this job, Delphi has a tool built in: [WebStencils](#), a template engine that Embarcadero introduced with [RAD Studio 12.2](#). You write regular HTML files, mark the places where data goes with an @, and let Delphi fill them in.

In this post, we will add our first WebStencils page to the existing server: a layout, a page that uses it, a loop over a list of objects, and a condition. By the end, the same executable will answer JSON on one URL and HTML on another.

What WebStencils is, and what it is not

Before we write templates, it helps to know where WebStencils sits. WebBroker has had a way to produce HTML for a very long time: the `TPageProducer` component, which replaces tags like `<#name>` in an HTML file by calling an event handler for each one. It works, and there are plenty of applications in production that use it. WebStencils is the modern successor. According to [Marco Cantù's introduction](#), its processor implements the

same interface as the page producer and can replace it, but the templates are far more expressive: they can read properties of Delphi objects directly, loop over lists, and share a common layout.

If you would like to see the two side by side, David Cornelius has published [a pair of WebBroker demos](#) that implement the same site with page producers and with WebStencils. I found it a very good way to understand what changed.

The flow of a WebStencils page is simple. The processor reads a template, looks up the data we registered under a name, and produces HTML.



WebStencils merges a template with named Delphi objects; the result is plain HTML

Note what the diagram does not contain: there is no JavaScript framework and no build step. The browser receives finished HTML. Also, WebStencils is not tied to WebBroker. The same processor works with RAD Server, and Marco points out that it can generate any text format, not just HTML.

WebStencils comes with two components. `TWebStencilsProcessor` renders one file. `TWebStencilsEngine` holds shared settings and can map URLs to template files. For our first page, the processor is all we need.

Step 1: The data for the page

WebStencils reads data from ordinary Delphi objects. We register an object under a name, and the template accesses its properties with `@name.Property`. Create a new unit `HelloPageModel.pas` with two small classes:

```
unit HelloPageModel;

interface

type
  TPageInfo = class
  private
    FTitle: string;
    FRenderedAt: string;
  public
    constructor Create(const ATitle: string);
    property Title: string read FTitle;
    property RenderedAt: string read FRenderedAt;
  end;

  TEndpoint = class
```

```

private
  FPath: string;
  FDescription: string;
  FIsHtml: Boolean;
public
  constructor Create(const APath, ADescription: string; AIsHtml: Boolean);
  property Path: string read FPath;
  property Description: string read FDescription;
  property IsHtml: Boolean read FIsHtml;
end;

implementation

uses
  System.SysUtils;

{ TPageInfo }

constructor TPageInfo.Create(const ATitle: string);
begin
  inherited Create;
  FTitle := ATitle;
  FRenderedAt := FormatDateTime('yyyy-mm-dd hh:nn:ss', Now);
end;

{ TEndpoint }

constructor TEndpoint.Create(const APath, ADescription: string;
  AIsHtml: Boolean);
begin
  inherited Create;
  FPath := APath;
  FDescription := ADescription;
  FIsHtml := AIsHtml;
end;

end.

```

`TPageInfo` carries the page title and the time the page was rendered. `TEndpoint` describes one URL of our server, and `IsHtml` tells us whether it returns HTML or JSON. There is really no magic here: plain classes with read-only properties. We do not need published properties or attributes; the official [WebStencils demos](#) use exactly this kind of class with public properties.

Step 2: The templates

Next, we write two HTML files in a folder named `templates`. The first one is the layout, the frame that every page of our site shares:

```

<!doctype html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title>@info.Title</title>
  <style>
    body { margin: 0; padding: 3rem 1.5rem; background: #f5f5f7; color: #1d1d1f;
      font: 17px/1.5 -apple-system, BlinkMacSystemFont, "Segoe UI", Helvetica, Arial, sans-serif;
    }
    main { max-width: 40rem; margin: 0 auto; padding: 2.5rem 3rem; background: #fff;
      border-radius: 18px; box-shadow: 0 4px 24px rgba(0, 0, 0, 0.06); }
    h1 { margin: 0 0 0.75rem; font-size: 2.25rem; font-weight: 700; letter-spacing: -0.02em; }
    p { color: #6e6e73; }
    a { color: #0066cc; text-decoration: none; }
    a:hover { text-decoration: underline; }
    ul { padding-left: 1.2rem; }
    li { margin: 0.4rem 0; }
    table { width: 100%; border-collapse: collapse; margin: 1.25rem 0; }
    th { text-align: left; font-size: 0.8rem; text-transform: uppercase;
      letter-spacing: 0.04em; color: #86868b; font-weight: 600; }
    th, td { padding: 0.65rem 0.5rem; border-bottom: 1px solid #e8e8ed; }
    tr:last-child td { border-bottom: 0; }
    hr { border: 0; border-top: 1px solid #e8e8ed; margin: 2rem 0 1rem; }
    small { color: #86868b; font-size: 0.8rem; }
  </style>
</head>
<body>
  <main>
    @RenderBody
    <hr>
    <small>Rendered by WebStencils at @info.RenderedAt -- write @@info to show a literal at
    sign.</small>
  </main>
</body>
</html>

```

Three things are worth pointing out:

1. `@info.Title` is replaced with the `Title` property of the object we register as `info`. That is the entire syntax for reading a value.
2. `@RenderBody` marks the place where the content of the actual page goes.
3. `@@` produces a literal `@`. You will need that more often than you think -- every email address and many CDN URLs contain one.

The `<style>` block only makes the page presentable, and WebStencils leaves it alone -- with one exception that illustrates point 3 nicely. WebStencils claims every `@` in a template, including the ones in CSS. When I added a `@media` rule, it arrived in the browser as `media.`, without any error message, just broken CSS. Write `@@media` instead.

The second file is the page itself. Save it as `templates/home.html`:

```

@LayoutPage layout
<h1>@info.Title</h1>
<p>This page and the JSON service run in the same Delphi process.</p>
<ul>
  @ForEach (var endpoint in endpoints) {
    <li>
      <a href="@endpoint.Path">@endpoint.Path</a> -- @endpoint.Description
      @if (endpoint.IsHtml) {
        (HTML)
      } @else {
        (JSON)
      }
    </li>
  }
</ul>

```

Again, the notes:

1. `@LayoutPage layout` in the first line says: render me inside `layout.html`. The name is given without the extension.
2. `@ForEach (var endpoint in endpoints) { ... }` repeats the block for every element in the list we register as `endpoints`. Inside, `endpoint` is the current element.
3. `@if (endpoint.IsHtml) { ... } @else { ... }` picks one of two blocks based on a boolean property.

Step 3: Render the page in the web module

Now we connect the templates with the web module from the previous post. We need one more route in the constructor:

```
AddRoute('/hello', mtGet, HomeAction);
```

We also need a helper that finds the templates, and the action handler itself. Add the units `System.IOUtils`, `System.Generics.Collections`, `Web.Stencils`, and `HelloPageModel` to the `uses` clause of the implementation section, and then add the following:

```

function TemplateFileName(const AName: string): string;
begin
  // the templates folder sits next to the executable
  Result := TPath.Combine(
    TPath.Combine(ExtractFilePath(ParamStr(0)), 'templates'), AName);
end;

```

```

procedure THelloModule.HomeAction(Sender: TObject; Request: TWebRequest;
  Response: TWebResponse; var Handled: Boolean);
var
  Processor: TWebStencilsProcessor;
  Endpoints: TObjectList<TEndpoint>;
begin
  Processor := TWebStencilsProcessor.Create(nil);
  try
    // (7) the page to render; it names its own layout
    Processor.InputFileName := TemplateFileName('home.html');

    // (8) the data -- True hands ownership to the processor
    Processor.AddVar('info', TPageInfo.Create('Hello from WebStencils!'), True);

    Endpoints := TObjectList<TEndpoint>.Create;
    Endpoints.Add(TEndpoint.Create('/hello/HelloService/Hello',
      'returns a greeting', False));
    Endpoints.Add(TEndpoint.Create('/hello/HelloService/Add?A=2&B=3',
      'adds two integers', False));
    Endpoints.Add(TEndpoint.Create('/hello', 'this page', True));
    Processor.AddVar('endpoints', Endpoints, True);

    // (9) Content runs the template engine and returns the HTML
    Response.ContentType := 'text/html; charset=utf-8';
    Response.Content := Processor.Content;
  finally
    Processor.Free;
  end;
end;

```

The numbers continue where the previous post left off:

1. `InputFileName` is the template to render. We point it to `home.html`, and the processor follows the `@Layout-Page` line to `layout.html` in the same folder on its own.
2. `AddVar` registers an object under a name. The third parameter, `True`, hands ownership to the processor: when we free the processor, it frees `info` and the list. Since `TObjectList<TEndpoint>` owns its elements, the endpoints are freed with it. No leaks, and no `try..finally` for each object.
3. Reading `Content` runs the engine and returns the finished HTML, which we pass to the response.

You might wonder why we create a new processor for every request instead of placing one on the web module. We could; the official demos do exactly that for their simpler examples. However, a fresh processor per request means that no data from one request can ever show up in the next. In my opinion, that guarantee is worth the small cost of creating one object per request, and for a first page, I prefer the version that cannot surprise me.

Finally, add `HelloPageModel` to the `uses` clause of `HelloServer.dpr`. The complete sources are listed at the end of this post.

Step 4: Run it

Compile and start the server. Before you open the browser, though, copy the `templates` folder next to `HelloServer.exe`. `TemplateFileName` looks for it there, and when you compile in the IDE, the executable ends up in an output folder like `Win32\Debug`, not next to your sources. I promise, this is the first error you will run into with `WebStencils`, and it has nothing to do with the templates themselves. Without the folder, `/hello` answers with a 500 and `WebBroker`'s default "Internal Application Error" page, which reads `Cannot create file "...\\templates\\home.html"`. The system cannot find the path specified. At least the message tells you exactly where the server looked -- but it tells every visitor, too, so do not leave it like that in production.

Internal Application Error

Cannot create file "C:\Projects\HelloServer\Win32\Debug\templates\home.html". The system cannot find the path specified

/hello

The first error you will meet: no `templates` folder next to the executable, and WebBroker answers with its default 500 page.

Now open <http://localhost:8080/hello>. The heading reads "Hello from WebStencils!", the list shows our three URLs, the last one marked as HTML, and the footer tells you when the page was rendered. Reload the page and the time changes: this is server-side rendering in its simplest form. The JSON URLs from the previous post work exactly as before -- and they are clickable now.

Hello from WebStencils!

This page and the JSON service run in the same Delphi process.

- </hello/HelloService/Hello> -- returns a greeting (JSON)
- </hello/HelloService/Add?A=2&B=3> -- adds two integers (JSON)
- </hello> -- this page (HTML)

Rendered by WebStencils at 2026-09-26 19:24:20 -- write @info to show a literal at sign.

The rendered page: `home.html` inside `layout.html`, with the loop, the condition, and the render time in the footer.

Before you render user input

In this post, all data comes from our own code. The moment a value comes from a request -- a query parameter, a form field, a database column a user filled in -- it matters whether the output is HTML-encoded, or a user can inject markup and script into your page. WebStencils HTML-encodes every @ value by default: a description of `<b>bold</b>` & "quoted" arrives in the browser as `<b>bold</b>` & `"quoted"`, which is also why the & in our Add link shows up as `&` in the page source. Only a backslash, as in `@\endpoint.Description`, switches encoding off -- so reserve that for HTML you produced yourself, never for anything a user typed.

Where this introduction ends

I kept this first page deliberately small, and WebStencils can do a lot more. There are `@Import` for reusable fragments, `@switch` for multi-way decisions, and access to the request through `@query`. Since RAD Studio 13, it also works with WebBroker's new session management and authentication components, which [Embarcadero's overview of the 13.0 changes](#) describes. The same overview mentions a whitelist that controls which members a template may access. Be aware that, out of the box, it only restricts `TDataSet` and `TStrings` descendants; every public property of your own classes stays readable until you configure `TWebStencilsProcessor.Whitelist` yourself -- worth doing when your objects carry data that should never end up in a page.

Alternatives

Server-side templates are not unique to Delphi, of course. In the Delphi open-source world, [DelphiMVCFramework](#) ships its own template engine, and mORMot includes an implementation of [Mustache](#), a logic-less template language with ports for many languages. Outside of Delphi, the same page would be a [Jinja](#) template in Python or a Razor page in [ASP.NET Core](#). If your team already knows one of these, the WebStencils syntax will feel familiar within minutes.

Takeaways

We added server-rendered HTML to our WebBroker server with two template files, a unit with two plain classes, and one action handler. WebStencils reads properties of registered objects with `@name.Property`, loops with `@ForEach`, decides with `@if`, and shares a frame between pages with `@LayoutPage` and `@RenderBody`.

A WebStencils page is HTML with a few `@` signs in it. The Delphi side only has to say which objects go by which names.

In the next post, we will replace the hard-coded list with real data: we will create an SQLite database in code -- file, table, and sample rows -- and render a table of customers straight from a FireDAC query. Until then, change the templates, add a property to `TPageInfo`, and see what happens. Enjoy!

Complete source code

For reference, here are the two files that changed compared to the previous post. The unchanged `HelloWebModule.dfm` and the templates are shown above.

```
program HelloServer;

{$APPTYPE CONSOLE}

uses
  System.SysUtils,
  Web.WebReq,
  IdHTTPWebBrokerBridge,
  HelloPageModel in 'HelloPageModel.pas',
  HelloWebModule in 'HelloWebModule.pas' {HelloModule: TWebModule};

const
  PORT = 8080;

var
  Server: TIdHTTPWebBrokerBridge;
begin
  try
```

```

// (1) tell WebBroker which class answers the requests
WebRequestHandler.WebModuleClass := THelloModule;

// (2) the HTTP server: Indy, bridged to WebBroker
Server := TIdHTTPWebBrokerBridge.Create(nil);
try
  Server.DefaultPort := PORT;
  Server.Active := True;

  WriteLn('WebBroker server running on port ', PORT);
  WriteLn('Try: http://localhost:8080/hello');
  WriteLn('Press Enter to stop. ');
  ReadLn;

  Server.Active := False;
finally
  Server.Free;
end;
except
  on E: Exception do
  begin
    WriteLn(E.ClassName, ': ', E.Message);
    ExitCode := 1;
  end;
end;
end.

```

```

unit HelloWebModule;

interface

uses
  System.SysUtils,
  System.Classes,
  System.JSON,
  Web.HTTPApp;

type
  THelloModule = class(TWebModule)
  private
    procedure AddRoute(const APathInfo: string; AMethod: TMethodType;
      AHandler: THTTPMethodEvent; ADefault: Boolean = False);
    procedure SendJson(Response: TWebResponse; AStatusCode: Integer;
      AJson: TJSONObject);
    procedure Cors(Sender: TObject; Request: TWebRequest;
      Response: TWebResponse; var Handled: Boolean);
    procedure HelloAction(Sender: TObject; Request: TWebRequest;
      Response: TWebResponse; var Handled: Boolean);
    procedure AddAction(Sender: TObject; Request: TWebRequest;
      Response: TWebResponse; var Handled: Boolean);
    procedure HomeAction(Sender: TObject; Request: TWebRequest;
      Response: TWebResponse; var Handled: Boolean);
    procedure NotFoundAction(Sender: TObject; Request: TWebRequest;
      Response: TWebResponse; var Handled: Boolean);
  public
    constructor Create(AOwner: TComponent); override;
  end;

implementation

uses
  System.IOUtils,
  System.Generics.Collections,
  Web.Stencils,
  HelloPageModel;

{$R *.dfm}

```

```

function TemplateFileName(const AName: string): string;
begin
    // the templates folder sits next to the executable
    Result := TPath.Combine(
        TPath.Combine(ExtractFilePath(ParamStr(0)), 'templates'), AName);
end;

{ THelloModule }

constructor THelloModule.Create(AOwner: TComponent);
begin
    inherited;

    // (1) runs before any action -- adds the CORS headers
    BeforeDispatch := Cors;

    // (2) one action per URL
    AddRoute('/hello/HelloService/Hello', mtGet, HelloAction);
    AddRoute('/hello/HelloService/Add', mtGet, AddAction);
    AddRoute('/hello', mtGet, HomeAction);

    // (3) the default action answers everything else
    AddRoute('', mtAny, NotFoundAction, True);
end;

procedure THelloModule.AddRoute(const APathInfo: string; AMethod: TMethodType;
    AHandler: THTTPMethodEvent; ADefault: Boolean);
var
    Item: TWebActionItem;
begin
    Item := Actions.Add;
    Item.PathInfo := APathInfo;
    Item.MethodType := AMethod;
    Item.Default := ADefault;
    Item.OnAction := AHandler;
end;

procedure THelloModule.SendJson(Response: TWebResponse; AStatusCode: Integer;
    AJson: TJSONObject);
begin
    try
        Response.StatusCode := AStatusCode;
        Response.ContentType := 'application/json; charset=utf-8';
        Response.Content := AJson.ToJSON;
    finally
        AJson.Free;
    end;
end;

procedure THelloModule.Cors(Sender: TObject; Request: TWebRequest;
    Response: TWebResponse; var Handled: Boolean);
begin
    // (4) CORS: '*' allows EVERY origin, which effectively switches the
    // browser's cross-origin protection off for this server. Fine for
    // development; in production, replace '*' with the origin of your
    // web application, e.g. 'https://app.example.com'.
    Response.SetCustomHeader('Access-Control-Allow-Origin', '*');

    // (5) answer the browser's preflight request right here
    if SameText(Request.Method, 'OPTIONS') then
    begin
        Response.SetCustomHeader('Access-Control-Allow-Methods', 'GET, OPTIONS');
        Response.SetCustomHeader('Access-Control-Allow-Headers', 'Content-Type');
        Response.StatusCode := 204;
        Handled := True;
    end;
end;

```

```

procedure THelloModule.HelloAction(Sender: TObject; Request: TWebRequest;
  Response: TWebResponse; var Handled: Boolean);
begin
  SendJson(Response, 200,
    TJSONObject.Create.AddPair('value', 'Hello from WebBroker!'));
end;

procedure THelloModule.AddAction(Sender: TObject; Request: TWebRequest;
  Response: TWebResponse; var Handled: Boolean);
var
  A, B: Integer;
begin
  // (6) nobody converts the parameters for us -- we do it ourselves
  if TryStrToInt(Request.QueryFields.Values['A'], A) and
    TryStrToInt(Request.QueryFields.Values['B'], B) then
    SendJson(Response, 200,
      TJSONObject.Create.AddPair('value', TJSONNumber.Create(A + B)))
  else
    SendJson(Response, 400,
      TJSONObject.Create.AddPair('error', 'A and B must be integers'));
end;

procedure THelloModule.HomeAction(Sender: TObject; Request: TWebRequest;
  Response: TWebResponse; var Handled: Boolean);
var
  Processor: TWebStencilsProcessor;
  Endpoints: TObjectList<TEndpoint>;
begin
  Processor := TWebStencilsProcessor.Create(nil);
  try
    // (7) the page to render; it names its own layout
    Processor.InputFileName := TemplateFileName('home.html');

    // (8) the data -- True hands ownership to the processor
    Processor.AddVar('info', TPageInfo.Create('Hello from WebStencils!'), True);

    Endpoints := TObjectList<TEndpoint>.Create;
    Endpoints.Add(TEndpoint.Create('/hello/HelloService/Hello',
      'returns a greeting', False));
    Endpoints.Add(TEndpoint.Create('/hello/HelloService/Add?A=2&B=3',
      'adds two integers', False));
    Endpoints.Add(TEndpoint.Create('/hello', 'this page', True));
    Processor.AddVar('endpoints', Endpoints, True);

    // (9) Content runs the template engine and returns the HTML
    Response.ContentType := 'text/html; charset=utf-8';
    Response.Content := Processor.Content;
  finally
    Processor.Free;
  end;
end;

procedure THelloModule.NotFoundAction(Sender: TObject; Request: TWebRequest;
  Response: TWebResponse; var Handled: Boolean);
begin
  SendJson(Response, 404,
    TJSONObject.Create.AddPair('error', 'Not found: ' + Request.PathInfo));
end;

end.

```

Free to read. Not free to make.

Every tutorial, article, and line of example code on Holger's Code is published without a paywall and without ads. This page is about what keeps it that way.

Professional work, published free

The content here is held to the same standard as professional client work: every tutorial is built as a real project, tested against current versions, documented step by step, and revisited when the frameworks move on. A single in-depth tutorial routinely takes days — and that's before the bills behind it: servers, storage, build infrastructure, licenses, and the hardware everything is verified on.

If an article or tutorial here has saved you an afternoon of debugging, taught you a technique, or helped you ship, it created real value for you. Supporting it isn't charity — it's paying for professional work you found useful, at whatever price you choose. And if you can't, keep reading anyway. That's what the free part means.

Ways to support

KO-FI

Buy me a coffee

A one-time tip — no account, no subscription, any amount.

BOOKS & COURSES

Buy the paid work

The paid tier of everything published free here — and you get something lasting in return.

SPREAD THE WORD

Share an article

Send a tutorial to a colleague, cite an article, subscribe to the RSS feed.

Nothing here goes behind a paywall, whether you chip in or not. But if something on this site earned its keep today, this is where to say so.

[Support on Ko-fi —](#)